

## LINDAX MP

### MULTI PURPOSE LITHIUM GREASE

#### Description

Grease Lithium MP are premium quality lithium soap thickened greases produced from low volatile high viscosity index mineral oils, superior fats/fatty acids, and a synergistic blend of additives and performance boosters.

#### Benefits

- Recommended for use in all general purpose industrial applications where grease lubrication is preferred.
- Provide optimum lubrication in bearings, sliding parts and mechanisms operating at moderate loads under ambient to medium temperatures up to 120°C.
- Can also be used as multipurpose wheel bearing and chassis greases in automotive applications.
- These greases are also suitable for lubrication of water pump bearings, machine tools, gears, couplings, and universal joints.



#### Typical Properties

		Lindax - MP 2	Lindax - MP 3
Code		GR0060001	GR0070001
Appearance		Light Coloured Translucent	Light Coloured Translucent
NLGI No		2	3
Structure		Smooth	Smooth
Soap Type		Lithium 12 Hydroxystearate	Lithium 12 Hydroxystearate
Worked penetration, at 25°C, 60/60 Strokes	mm-1	265-295	220-250
Base Oil viscosity at 100°C	cSt	10-16	10-16
Drop Point	°C	180	180
Rust Test max		1	1
Roll Stability test penetration change, after 16hrs	%	<25	<25
Operating temperature	°C	-12/130	-20/130